WHAT IS CLAIMED IS:

- A method for selecting a wireless serving node, comprising:
- 5 receiving a wireless registration request at a wireless serving node;

determining whether the serving node is managing a wireless session associated with the registration request;

generating a wireless session inquiry for a group of associated wireless serving nodes if the serving node is not managing a wireless session associated with the registration request;

receiving a wireless session response containing a serving node identifier; and

generating a wireless registration response containing the serving node identifier.

2. The method of Claim 1, further comprising:

20 determining whether the registration request is associated with an active wireless session; and

initiating the establishment of a wireless session if the registration request is not associated with an active wireless session.

25

15

3. The method of Claim 2, wherein determining whether the registration request is associated with an active wireless session comprises examining a Mobility Event Indication in the registration request.

15

20

- 4. The method of Claim 1, further comprising generating a wireless registration response indicating acceptance of the registration request if the serving node is managing a wireless session associated with the registration request.
- 5. The method of Claim 1, further comprising: determining the time elapsed since generating the wireless session inquiry; and
- initiating the establishment of a wireless session 10 if a predetermined amount of time has elapsed.
 - The method of Claim 1, wherein the wireless 6. registration request comprises an All-Registration Request.
 - The method of Claim 1, wherein determining 7. whether the serving node is managing a wireless session associated with the registration request comprises searching table containing information wireless sessions being managed by the serving node.
- The method of Claim 1, wherein at least one of 8. the wireless session inquiry and the wireless session 25 response comprise a multicast message.

062891.0661

- The method of Claim 1, wherein the wireless 9. inquiry comprises International session an Subscriber Identifier and an Access Network Identifier.
- 10. The method of Claim 1, wherein the registration 5 response containing the serving node identifier comprises a wireless registration response indicating denial of the registration request.

15

39

A system for selecting a wireless serving node, comprising:

means for receiving a wireless registration request at a wireless serving node;

means for determining whether the serving node is 5 a wireless session associated with the managing registration request;

means for generating a wireless session inquiry for a group of associated wireless serving nodes if the is not managing a wireless session serving node associated with the registration request;

means for receiving a wireless session response containing a serving node identifier; and

for generating a wireless registration means response containing the serving node identifier.

The system of Claim 11, further comprising:

for determining whether the registration request is associated with an active wireless session;

20 and

> means for initiating the establishment of a wireless session if the registration request is not associated with an active wireless session.

The system of Claim 12, wherein determining 25 13. whether the registration request is associated with an active wireless session comprises examining a Mobile Event Identifier in the registration request.

15

20

- The system of Claim 11, further comprising means for generating a wireless registration response indicating acceptance of the registration request if the serving node is managing a wireless session associated with the registration request.
- The system of Claim 11, further comprising: for determining the time elapsed since means generating the wireless session inquiry; and
- means for initiating the establishment of a wireless 10 session if a predetermined amount of time has elapsed.
 - The system of Claim 11, wherein the wireless 16. registration request comprises an All-Registration Request.
 - The system of Claim 11, further comprising means for storing information regarding wireless sessions being managed by the serving node, wherein determining whether the serving node is managing a wireless session registration request associated with the comprises searching the means.
- The system of Claim 11, wherein at least one of 25 the wireless session inquiry and the wireless session response comprise a multicast message.

- The system of Claim 11, wherein the wireless International session inquiry comprises an Mobile Subscriber Identifier and an Access Network Identifier.
- Claim wherein the 5 20. The system of 11, registration response containing the serving node identifier comprises a wireless registration response indicating denial of the registration request.

15

42

A set of logic for selecting a wireless serving node, the logic encoded in media and operable to:

receive a wireless registration request wireless serving node;

determine whether the serving node is managing a 5 wireless session associated with the registration request;

generate a wireless session inquiry for a group of associated wireless serving nodes if the serving node is not managing a wireless session associated with the registration request;

receive a wireless session response containing a serving node identifier; and

generate a wireless registration response containing the serving node identifier.

The logic of Claim 21, wherein the logic is further operable to:

determine whether the registration request 20 associated with an active wireless session; and

initiate the establishment of a wireless session if the registration request is not associated with an active wireless session.

25 The logic of Claim 22, wherein determining whether the registration request is associated with an active wireless session comprises examining a Mobile Event Identifier in the registration request.

20

Attorney's Docket 062891.0661

43

- 24. The logic of Claim 21, wherein the logic is further operable to generate a wireless registration response indicating acceptance of the registration request if the serving node is managing a wireless session associated with the registration request.
- 25. The logic of Claim 21, wherein the logic is further operable to:

determine the time elapsed since generating the 10 wireless session inquiry; and

initiate the establishment of a wireless session if a predetermined amount of time has elapsed.

- 26. The logic of Claim 21, wherein the wireless 15 registration request comprises an All-Registration Request.
 - 27. The logic of Claim 21, wherein determining whether the serving node is managing a wireless session associated with the registration request comprises searching a table containing information regarding wireless sessions being managed by the serving node.
- 28. The logic of Claim 21, wherein at least one of the wireless session inquiry and the wireless session response comprise a multicast message.

... I come a product and come and come

44

- 29. The logic of Claim 21, wherein the wireless session inquiry comprises an International Mobile Subscriber Identifier and an Access Network Identifier.
- 5 30. The logic of Claim 21, wherein the wireless registration response containing the serving node identifier comprises a wireless registration response indicating denial of the registration request.

10

15

45

A method for selecting a wireless serving node, comprising:

receiving, at a wireless serving node, a wireless session inquiry from an associated wireless serving node;

determining whether the serving node is managing a wireless session associated with the session inquiry;

generating a wireless session response containing an identifier for the serving node if the serving node is managing a wireless session associated with the session inquiry.

- The method of Claim 31, further comprising: 32. receiving a wireless registration request associated with the session response; and
- wireless registration generating a response indicating acceptance of the registration request.
- Claim 33. The method of 32, wherein the registration request comprises an All-Registration 20 Request.
 - The method of Claim 31, further comprising:

determining whether the serving node is associated the network from which with the session inquiry originated; and

generating a wireless session response containing an identifier for the serving node only if the serving node is associated with the network from which the session inquiry originated.

The method of Claim 34, wherein determining whether the serving node is associated with the network from which the session inquiry originated comprises examining a network identifier in the inquiry.

5

15

20

25

- The method of Claim 35, wherein the network 36. identifier comprises an Access Network Identifier.
- The method of Claim 31, wherein at least one of 37. the session inquiry and the session response comprise a 10 multicast message.
 - The method of Claim 31, wherein determining whether the serving node is managing a wireless session associated with the session inquiry comprises searching a table containing information regarding wireless sessions being managed by the serving node.
 - The method of Claim 31, further comprising: determining the time elapsed since receiving the wireless session inquiry; and

generating a second wireless session inquiry if a predetermined amount of time has elapsed, the second wireless inquiry directed to a different group of serving nodes than the first wireless session inquiry.

The method of Claim 39, further comprising:

determining whether a wireless session response associated with the second session inquiry has been received; and

relaying the session response to the group of 5 serving nodes from which the first session inquiry originated if the session response has been received.

15

30

48

A set of logic for selecting a serving node, the logic encoded in media and operable to:

receive a wireless session inquiry at a wireless serving node;

5 determine whether the serving node is managing a wireless session associated with the session inquiry;

generate a wireless session response containing an identifier for the serving node if the serving node is managing a wireless session associated with the session inquiry.

The logic of Claim 41, wherein the logic is 42. further operable to:

receive a wireless registration request associated with the session response; and

generate a wireless registration response indicating acceptance of the registration request.

- The logic of Claim 42, wherein the registration request comprises an All-Registration Request. 20
 - The logic of Claim 41, wherein the logic is 44. further operable to:

determine whether the serving node is associated 25 the network from which the session originated; and

generate a wireless session response containing an identifier for the serving node only if the serving node is associated with the network from which the session inquiry originated.

49

- The logic of Claim 44, wherein determining whether the serving node is associated with the network from which the session inquiry originated comprises examining a network identifier in the inquiry.
- The logic of Claim 45, wherein the network identifier comprises an Access Network Identifier.
- The logic of Claim 41, wherein at least one of 10 the session inquiry and the session response comprise a multicast message.
- The logic of Claim 41, wherein determining whether the serving node is managing a wireless session 15 associated with the session inquiry comprises searching a table containing information regarding wireless sessions being managed by the serving node.
- 20 The logic of Claim 41, wherein the logic is 49. further operable to:

determine the time elapsed since receiving the wireless session inquiry; and

generate a second wireless session inquiry if 25 predetermined amount of time has elapsed, the second wireless inquiry directed to a different group of serving nodes than the first wireless session inquiry.

50

50. The logic of Claim 49, wherein the logic is further operable to:

determine whether a wireless session response associated with the second session inquiry has been received; and

relay the session response to the group of serving nodes from which the first session inquiry originated if the session response has been received.

51. A method for selecting a wireless serving node, comprising:

detecting the presence of a mobile unit at a wireless packet control function;

5 determining an identifier for a wireless serving node that could potentially service the mobile unit;

generating a wireless registration request containing the identifier;

receiving a wireless registration response;

determining whether the registration response indicates that the registration request is accepted;

determining whether the registration response a wireless serving node identifier if the does not indicate that the registration response registration request is accepted; and

generating, if the registration response does not indicate that the registration request is accepted and contains a wireless serving node identifier, a wireless registration request containing the identifier.

20

10

15

52. The method of Claim 51, wherein determining an identifier for a wireless serving node that could potentially service the mobile unit comprises analyzing an identifier of the mobile unit.

25

53. The method of Claim 51, wherein the wireless registration request comprises an All-Registration Request.

- 54. The method of Claim 51, further comprising generating a message regarding the wireless session if the registration request is accepted.
- 5 55. The method of Claim 51, wherein the registration response containing the wireless serving node identifier indicates that the registration request is denied.

062891.0661

53

A set of logic for selecting a serving node, the logic encoded in media and operable to:

detect the presence of a mobile unit;

determine an identifier for a wireless serving node that could potentially service the mobile unit; 5

generate a wireless registration request containing the identifier;

receive a wireless registration response;

registration determine whether the response indicates that the registration request is accepted;

determine whether the registration response contains a wireless serving node identifier if the registration response does not indicate that the registration request is accepted; and

- generate, if the registration response does not 15 indicate that the registration request is accepted and contains a wireless serving node identifier, a wireless registration request containing the identifier.
- The logic of Claim 56, wherein determining an 20 57. identifier for a wireless serving node that potentially service the mobile unit comprises analyzing an identifier of the mobile unit.
- The logic of Claim 56, wherein the wireless 25 58. comprises All-Registration registration request an Request.

- 59. The logic of Claim 56, wherein the logic is further operable to generate a message regarding the wireless session if the registration request is accepted.
- 5 60. The logic of Claim 56, wherein the registration response containing the wireless serving node identifier indicates that the registration request is denied.

15

20

25

55

A method for selecting a wireless serving node, comprising:

receiving an All-Registration Request at a wireless serving node;

Mobile Event Identifier in the 5 examining a determining the registration request to whether associated with registration request is an wireless session;

initiating the establishment of a wireless session if the registration request is not associated with an active wireless session;

searching a table containing information regarding wireless sessions being managed by the serving node to determine whether the serving node is managing a wireless session associated with the registration request if the registration request is associated with active an wireless session;

generating an All-Registration Reply indicating acceptance of the registration request if the serving node is managing a wireless session associated with the registration request;

generating a multicast message containing a wireless session inquiry for a group of associated wireless serving nodes if the serving node is not managing a wireless session associated with the registration the wireless session inquiry including request, International Mobile Subscriber Identifier and an Access Network Identifier;

determining the time elapsed since generating the 30 wireless session inquiry;

10

15

20



Attorney's Docket 062891.0661

56

initiating the establishment of a wireless session if a predetermined amount of time has elapsed;

receiving a multicast message including a wireless session response containing a serving node identifier;

generating an All-Registration Reply indicating denial of the registration request and containing the serving node identifier;

receiving a multicast message containing a wireless session inquiry from an associated wireless serving node;

searching the table to determine whether the serving node is managing a wireless session associated with the session inquiry;

determining whether the serving node is associated with the network from which the session inquiry originated if the serving node is managing a wireless session associated with the session inquiry; and

generating a wireless session response containing an identifier for the serving node if the serving node is managing a wireless session associated with the session inquiry and if the serving node is associated with the network from which the session inquiry originated.